

Haydon's range of multi way metal cased PSUs use the latest technology PTC fuses, eliminating replacing fuses after overvoltage or short circuit occurs

When traditional fuses are being used for overcurrent protection it can only protect once then it must be replaced. The PTC resettable fuse is a new-type of overcurrent protection element which has two functions providing overcurrent protection and automatic reset. The overcurrent protection PTC element is serially connected to the circuit and under normal circumstances it provides a low resistance state and can ensure the normal working of the circuit. If a short circuit or unusually high current occurs, the PTC fuses cut in to reduce the voltage down to a trickle thus preventing damage and protecting the equipment. The PTC fuse will automatically reset once the fault in the overcurrent is removed. The PTC elements will automatically return to its low resistance state, which not only avoids maintenance or replacement but also avoids a continuously circulating switching state which can cause circuit damage.



12vDC Metal Boxed Multi Output c/w BB

	HAY-PSU412-5A BB 7AH	HAY-PSU812-5A BB 7AH
Input Voltage	187 – 253V Rated 3amp main fuse	187 – 253V Rated 3amp main fuse
Outputs	4 x 12VDC Outputs	8 x 12VDC Outputs
Maximum Output	5 Amps	5 Amps
Auto Reset PTC Fuse for each Output	Maximum Per Output 1.1 Amps **Not exceeding 5 Amps Total Output**	Maximum Per Output 1.1 Amps **Not exceeding 5 Amps Total Output**
Surge Protected		
Additional Current for Battery Charging		
Charging Current	13.8 VDC	13.8 VDC
Recommended Battery	7Amp Hour Battery not Included	7Amp Hour Battery not Included
Battery Deep Discharge Protection		
Internal ON/OFF Power Switch		
Individual LED Output Indicator		
Dimensions	8 x 28.5 x 25.5 cm Weight 3.0 Kgs	8 x 28.5 x 25.5 cm Weight 3.0 Kgs
CE & RoHS Compliant		
All Models: Storage Temperature - 20 to 85C; Operating Temperature -10 to 50C; Operating Relative Humidity 0-90% Non Condensing		