

HAY-DC JACK PLUG MALE

Male DC Jack Plug Adapter

DC Jack plugs in both male and female versions. Using these units prevents cutting leads on PSUs & cameras



HAY-DC JACK PLUG FEMALE

Female DC Jack Plug Adapter

DC Jack plugs in both male and female versions. Using these units prevents cutting leads on PSUs & cameras



HAY-RJ45-TERM

RJ45 to Terminal connector

RJ45 to screw terminal adapter. Can be used for any RJ45 Application. It is wired in accordance with EIA/TIA 568B wiring standard for structured cabling



HAY-GLI

BNC Ground Loop isolator

Ground Loop Isolator
Fully surge protected
Built in transient protection
Connect directly to you camera or DVR



HAY-VB01-PT-GLI

Cat5e/6 Video Balun with Built in Ground loop Isolator

Ground loop isolator Balun -Twin pack
160mm Pigtail for easy connection to equipment
Fully surge protected with Screwless terminal block for fast install.
400m Transmission Distance Passive to passive connection. Up to 800m using a Haydon Active receiver



HAY-BNC60 & HAY-BNC100

60cm & 1m BNC to BNC Patch cords with RG174 and sleeved BNCs

This useful 60cm BNC patch lead allows fast, economical & safe connection from the VB hub units to your DVR without unnecessary making up of short leads



HAY-LED

5mm Flashing LED Module

5mm RED flashing LED, c/w 6" lead from circuit board to 2 x AA battery holder.



HAY-WSA4 & HAY-WSA3

CCTV Warning Signs

Data compliant CCTV Warning Sign
A4 - W210mm x L297mm
A3 - W297mm x L420mm



HAY-BRKT

Dual length camera mounting bracket

Internal dual length camera bracket 100mm to 160mm. All metal construction.
Wall or ceiling mount**(subject to top mount on camera body)**

