

Features

No Power Supply Needed

Transmits up to 600ft (VGA 640x480)
over single UTP CAT5e/6 Cable

Supported resolutions: VGA, SVGA, XGA,
SXGA & WXGA

Benefits

- Eliminates costly and bulky VGA cable
- Ultra compact size for installation versatility.
- Carry Video from DVR, PC or other VGA sources to remote displays or distribution locations utilizing cost effective CAT5 cable
- Allows a simple and cost effective solution for extending distance for VGA monitors



Quick Setup Guide

Plug your VGA cable from the VGA output into the Transmit Baluns HD15 connector. Secure the cables using the lock down screws. Make a similar connection between the Receive Baluns HD15 connector and your display. Insert the CAT5 cable into both ends of the Baluns. You may use standard EIA 568A/B termination.

NOTE: Baluns are interchangeable for transmit or receive functions.
Compatibility: Does not support VGA handshaking (DDC) information.

Technical Specifications

Signal: VGA, VESA VP&D 1.0, VIP ver 2.0

Bandwidth: DC to 60 MHz

Maximum Distance*:

VGA: (640 x 480) 600ft.

SVGA : (800 x 600) 400ft.

XGA : (1024x768) 350ft.

WXGA : (1280x768) 250ft.

SXGA : (1280x1024) 250ft.

UXGA : (1600x1200) 200ft.

WUXGA: (1920x1200) 200ft.

(*Longer distances are possible but best quality is attained at shorter distances)

Maximum Video Input Level: 1.1Vp-p

Insertion Loss per Pair of Baluns: Less than 3dB over frequency range.

Video Impedance:

Input: RGB 75Ω (HD15) Unbalanced.

Output: RGB 100Ω (RJ45 shielded) Balanced

Cable (UTP): CAT5e/6 24 Gauge or lower solid copper twisted pair.

Connectors: One (1) VGA (HD15) Female for Video, One (1) RJ45 jack

General:

Dimensions: 65*55*25mm

Weight: 80g

Enclosure: ABS engineering plastic

Accessories: VGA cable

Operating Temperature: 0 °C to 55 °C

RJ45 Pinout:

Pin #1 = Blue +

Pin #2 = Blue -

Pin #3 = V Sync

Pin #4 = Green

Pin #5 = Green -

Pin #6 = H Sync

Pin #7 = Red +

Pin #8 = Red